

24" STAND-ON AERATOR

**LEGENDARY STRENGTH.
INCREASED MANEUVERABILITY.
PRODUCTIVITY MEANS PROFITABILITY.**



Exmark's new compact 24" Stand-On Aerator gives operators even more maneuverability making it possible to access smaller yards, more quickly—without operator fatigue. With drive speeds up to 6.8 miles per hour, it can aerate nearly 1.4 acres¹ per hour.

FEATURES:

- Equipped with a Kohler® CH440 Command® engine.
- 24-inch working width with 36 self-cleaning coring tines.
- Hydro-Gear® ZT-3100 transmission.
- Simple, intuitive controls—similar to commercial mowers—give landscape pros easy operation, zero-turn agility, precise control and fatigue-reducing ergonomics.
- Core depth of 0.5-inch to 5-inches set with electronic depth control.



ELECTRONIC DEPTH CONTROL

With the ability to easily set tine depth between 0.5" and 5", the Electronic Depth Control allows operators to maintain consistent core quality around a property.



GO ANYWHERE

The 24-inch Stand-On Aerator has a total width of 35.5-inches, giving it the ability to fit through a 36-inch gate. This makes it possible to access more yards, more quickly, without fatigue typically experienced on a small walk-behind aerator.



SPREADER ATTACHMENT

With an 80 pound seed capacity, the spreader attachment enables landscape pros to offer over-seeding in conjunction with aeration programs. The versatility significantly increases the productivity in revenue potential of the machine. (shown on 30" model)

The mowers landscape professionals trust 2 to 1.*

exmark.com

*Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x Aerating width x 0.44 | 80% efficiency: MPH x Aerating width x 0.352. *Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



24" STAND-ON AERATOR

| MODEL | ENGINE | WORKING WIDTH | WEIGHT | DIMENSIONS (W X H X L) |
|----------------|--------------|---------------|----------|------------------------|
| ARX440CKC24000 | CH440 Kohler | 24" | 979 lbs. | 35.5" x 51.0" x 68.6" |



SPECIFICATIONS

Engine – CH440 Kohler electric start engine governed to 3,800 rpm.

Transmission – Hydro-Gear ZT-3100.

Fuel Capacity – 1.85 gallons (7.0-L).

Working Width – 24".

Aerating Speed – 0 to 6.8 mph (11.0 kmph) forward.

Rear Tires – 16 x 4-8

Front Tires – 11 x 4-5 semi-pneumatic.

Drive – #50 chain.

of Tines – 36 coring tines.

Core Depth – 0.5" to 5" set with electronic depth control.

Plugs/square foot – 4.6.

ACCESSORIES & OPTIONS

Stand-On Aerator Spreader Attachment

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.