



# COMMERCIAL 21 S-SERIES

PRODUCTIVITY. COMMERCIAL DURABILITY. EASE OF USE.

## FEATURES

**5-inch Deep Cast Aluminum Cutting Deck**  
*2-in-1: Bag and Mulch*

**Commercial-Grade Engines**  
*Kawasaki®*

**Patented Front Height Adjustment System**  
*Eliminates need for pivot-style adjusters*

**Infinite Speed Control**  
*Multi-zone transmission provides infinite speed control from zero to 4.2 mph*

**Multiple Blade Options**  
*The option of five blade choices gives you the flexibility to customize for your unique cutting conditions.*



### EASE OF USE

The Commercial 21 has simple, straightforward controls and a lightweight, durable cast aluminum cutting deck, which reduces weight and eases maneuverability.



### THE EXMARK® SIGNATURE CUT

The true test of a mower is the cut quality it delivers. The Commercial 21 is engineered to consistently deliver an unmatched quality of cut, whether mulching or bagging. A variety of optional blades let you further optimize performance for your specific cutting conditions.

## TOP ACCESSORIES

Coated Bail Drive  
Deck Wear Kit  
Door Handle Kit  
Engine Guard  
Mulch Plug

Accessories may not fit each mower model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

[exmark.com](http://exmark.com)

# COMMERCIAL 21 S-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECS180GKA21000	FJ180V Kawasaki	21"	Self-Propelled Zone	123 lbs.	22.0" x 38.0" <sup>1</sup> x 62.0" <sup>1</sup>

<sup>1</sup> Varies with 0.5" cutting selections.



## POWER COMPONENTS

**Engine** – FJ180V Kawasaki engine governed to 3,300 rpm.

**Air Filter** – Dual element air cleaner.

**Drive System** – Self-propelled, rear-wheel gear-driven.

**Transmission** – Infinitely variable speed selection, dual wheel drive.

**Fuel Capacity** – 2-quart integral fuel tank.

**Speed** – 0.0 mph to 4.2 mph (6.6 kmph) forward.

**Speed Control** – Finger-tip control.

## DECK

**Style** – Fixed-deck, rear-discharge bagger standard with option to mulch.

**Widths Available** – 21" (53.3 cm).

**Cutting Height** – 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

**Blade** – 1 blade at 20.5".

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Engine Deck** – 5-inch-deep, 1/4-inch thick die-cast aluminum.

**Drive Tires** – 9 x 2.5, semi-pneumatic.

**Safety Package** – Zone start.

**Bag Capacity** – 2.5 bushels (20 gallons).

## ACCESSORIES & OPTIONS

Coated Bail Drive, Deck Wear Kit, Engine Guard and Mulch Plug

## WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

<sup>1</sup> Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

<sup>2</sup> For complete details, visit [exmark.com](http://exmark.com) or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.