

COMMERCIAL 30
S-SERIES

**UNMATCHED PERFORMANCE.
MANEUVERABILITY.
COMMERCIAL DURABILITY.**



Don't let its size fool you. Our Commercial 30 mower is deceptively light and easy to maneuver. In fact, it feels and handles much like its Commercial 21 counterparts. The major difference: its 30-inch cut delivers up to a 40% increase in cutting efficiency compared to a standard 21-inch mower—without wearing out the machine or its operator.

FEATURES:

- Equipped with Kawasaki® engine.
- 30-inch cutting width allows operators to cut 40-percent more with each pass than a 21-inch walk-behind mower.
- 2-in-1 cutting deck enables operators to quickly switch between bagging or mulching—without tools.
- Ground speeds up to 4.2 mph.
- Has a large-capacity 2.5 bushel bagger, reducing the number of stops.



TIMED TWO-BLADE CUTTING SYSTEM

The blade design works in conjunction with the cutting system to provide optimal cut quality in each of the three cutting modes - bagging, mulching or side-discharge. The time-blade system also reduces horsepower requirement.



EASE OF USE

With simple controls, patented front-height adjustment system and an easy to use single-point rear height adjust, the Commercial 30 is easy to use and eliminates the need for ongoing maintenance or repair.



PATENTED FRONT HEIGHT ADJUST

Simple, innovative and built to last, the Commercial 30's patented front height adjustment eliminates the need for pivot-style adjusters.

The mowers landscape professionals trust 2 to 1.*

exmark.com

*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



COMMERCIAL 30

S-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECS180CKA30000	FJ180V Kawasaki KAI	30"	Self-propelled	177 lbs.	31.9" x 38.25" ¹ x 68.0" ¹

¹ With handle in medium position. Varies with 0.5" cutting selections.



POWER COMPONENTS

Engine – FJ180V Kawasaki KAI engine; governed to 3,500 rpm.
Air Filter – Dual element air cleaner.
Drive System – Self-propelled, rear-wheel gear-driven.
Transmission – Infinitely variable speed selection.
Fuel Capacity – 1 gallon (3.8-L) fuel tank.
Speed – 0.0 mph to 4.2 (6.6 kmph) mph forward.
Speed Control - Finger-tip control.

DECK

Style – Fixed-deck. Ability to rear bag, side-discharge or mulch.
Widths Available – 30" (76 cm).
Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.5" (1.3 cm) increments.
Blade – 2 blades at 15.4".
Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 4.6-inch-deep stamped steel with welded reinforcement.
Front Tires – 9 x 2.5, semi-pneumatic.
Drive Tires – 10 x 3.0, semi-pneumatic.
Safety Package – Blade Brake Clutch (BBC).
Bag Capacity – 2.5 bushels (20 gallons).

ACCESSORIES & OPTIONS

Mulch Kit.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.