

SPREADER-SPRAYER

**INCREASED VERSATILITY.
EASY TO MANEUVER.
IMPROVED PROFITABILITY.**



Exmark's Spreader-Sprayer is far and away the most advanced machine in its category. Extremely easy to operate and maneuver, it features our most advanced lean-to-steer technologies, outstanding versatility and amazing stability—even on hillsides. Couple that with outstanding durability and you have a spreader-sprayer that is built to last.

FEATURES:

- Equipped with a Kohler® CH395 Command PRO® engine.
- The agitation system allows for both wettable powder and dry flow-ables.
- No belt hassle with the direct drive to transaxle and electric spinner motor and pump.
- Hopper can hold 175 lbs. An extra 50 pound bag can also be placed in carrier on top of tank.
- Stainless steel operator platform with isolation mounts for a more comfortable ride. Locks up or down for storage.



AGITATION SYSTEM

The in-tank agitation system keeps materials in suspension for more even, consistent coverage. This allows operators to use a wider range of materials, from flowable solids to wettable powders.



MANEUVERABILITY

Our innovative lean-to-steer technology design allows the operator to control all motion with just one hand. Allowing the operator to easily maneuver around properties with reduced effort.



SPREADER ATTACHMENT

Everything you need is right at your fingertips—allowing you to make easy adjustments while maintaining total control.

The mowers landscape professionals trust 2 to 1.*

exmark.com

*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).



SPREADER-SPRAYER

MODEL	ENGINE	WEIGHT	DIMENSIONS (W X H X L)
SSS395CKC00000	Kohler CH395	561 lbs.	35.5" x 51.5" x 67.5"



POWER COMPONENTS

Engine – Kohler CH395 Command Pro. Engines governed to 3,600 rpm.

Displacement – 277cc

Transmission – Hydrostatic

Drive System – Tuff Torq.

Fuel Capacity – 1.85 gallons (6.02-L).

Ground Speed – 0–5.5 mph (8.8 km/h) forward, 0–4.0 mph (6.4 km/h) reverse.

Front Tires – 13 x 6.5–6.

Rear Tires – 18 x 7.5–8

Frame – Stainless Steel

SPREAD AND SPRAY SYSTEM

Spread Width – Adjustable from 4 ft. up to 22 ft.

Hopper Capacity – 175 lbs, plus 50 lbs on spray tank.

Spinner Motor – 12 VDC, 2 hp motor.

Tank Capacity – 20 gallons.

Spray Width – Wide spray up to 11 ft wide. Narrow spray up to 5 ft wide

Spray Rate –

Wide: 0.69 gpm at 30 psi, 0.80 gpm at 40 psi

Narrow: 0.35 gpm at 30 psi, 0.40 gpm at 40 psi

Pump – Remco

ACCESSORIES & OPTIONS

15 ft Hose Tray, 30 Ft Hose and Tray, Anti-Siphon Assembly, Cable Guard Assembly, Hopper Screen (large and small hole), Multi-Purpose Bag, Spray Nozzles and Spray Wands.



EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2019 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2019.