

# VIKING®

## ENHANCED CONTROL SYSTEM. SEAMLESS PERFORMANCE. VERSATILE MOWER.



When you're ready to step up to the precise control and seamless performance of a hydro drive walk-behind, it's time for a Viking®. With its unique blend of features, technology and value, the Viking is the mower of choice of discerning landscape professionals with a keen eye on the bottom line.

### FEATURES:

- Equipped with Kawasaki® engines.
- UltraCut™ Series 2 deck with 36-inch cutting width. UltraCut Series 3 deck with 48-inch cutting width.
- Two Hydro-Gear® variable displacement pumps.
- Ground speeds up to 6.2 mph.
- Features Exmark's exclusive Enhanced Control System (ECS).



### TRACKING KNOB

Exmark's Hydro Quick Track Adjustment allows easy and fast adjustment without tools.



### OPERATOR FRIENDLY

The hydro-drive Viking is easy to operate, with instant forward-to-reverse and infinite speed control. Works at speeds up to 6.2 mph and 2.2 mph in reverse.



### EXCEPTIONAL TRACTION

The Viking comes with large, 16 x 6.5-8 tires that provide extra grip while smooth-tread, semi-pneumatic front caster tires eliminate flats.

The mowers landscape professionals trust 2 to 1.\*

[exmark.com](http://exmark.com)

\*Trusted 2-to-1 over the next best-selling brand of zero-turn mowers. Based on U.S. Data study by Wiese Research Associates Inc. Market Share and Additional Equipment Study (February 2016).





MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
VHS481GKA36200	FS481V Kawasaki V-Twin	36"	UltraCut Series 2	573 lbs	47.0" x 43.2" x 77.7"
VHS481GKA48300	FS481V Kawasaki V-Twin	48"	UltraCut Series 3	633 lbs	57.9" x 43.2" x 72.3"



## POWER COMPONENTS

**Engine** – FS481V Kawasaki V-Twin engine governed to 3,600 rpm.

**Drive System** – Two Hydro-Gear® variable-displacement pumps and two high-efficiency Parker/Ross wheel-drive motors with 1" (2.54 cm) tapered shafts.

**Hydro Fluid** – Exmark Premium Hydro Oil.  
**Speed** – Infinitely variable selection from 0–6.2 mph (10.0 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.

**PTO Engagement** – Mechanical blade engagement with blade brake.

**Fuel Capacity** – 5-gallon (18.9-L) fuel tank.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Deck Lift** – Manual cutter housing and front caster spacer position adjustment.

## DECK

**Style** – Fixed-deck, side-discharge standard with molded discharge chute and option to bag or mulch. UltraCut™ Series 2 on 36" unit and UltraCut Series 3 on 48" unit.

**Deck Construction** – 10-gauge top that is formed and continuously seam-welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations for improved strength.

**Widths Available** – 36" (91.4 cm) or 48" (121.9 cm).

**Cutting Height** – 1.0" (2.5 cm) to 4.25" (10.8 cm) in 0.25" (0.54 cm) increments.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 5.40"-diameter cutter housing and 1.0"-diameter spindle tube.

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Engine Deck** – 7-gauge, heavy-duty welded steel.

**Steering and Motion Control** – Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.

**Casters** – .38" thick caster yoke arms.

**Front Caster Tires** – Double-yoke, 9 x 3.5–4, smooth tread, semi-pneumatic.

**Drive Tires** – 16 x 6.5–8, 4-ply Turf Master.

**Tracking Adjustment** – Insta-Track.

**Turning Radius** – True zero-turn.

**Safety Package** – Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator's position without stopping engine.

**Parking Brake** – Lever-actuated mechanical compression.

## ACCESSORIES & OPTIONS

3-Bushel Bagger, Equipment Cover, Micro-Mulch System, Operator Controlled Discharge (Hand), StandOn and Weight Kit.

## WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Viking® are registered trademarks of Exmark Mfg. Co., Inc. Exmark is purchased 2 to 1 over the next best-selling brand of zero-turn mowers based on U.S. Data study by Wiese Research Associates, Inc. Market Share and Additional Equipment Study (February 2016). ©2020 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2020. Rev 1.