



# QUEST® E-SERIES

## PREMIUM RESIDENTIAL RIDER. SUPERIOR COMFORT AND VALUE.

### FEATURES

#### Series 2 Deck

Side Discharge: 42 | 50

#### Engine

Kohler®

#### Superior Comfort

Ergonomic seat system

#### Foot-Lift Assist

Standard on 50" to help ease lifting and lowering the cutting deck

#### Single-Point Height Adjust

Easily to vary the Quest's cutting deck



### COMMERCIAL-GRADE FEATURES

Exmark's Quest is a premium entry-level zero-turn mower. The proven commercial features have been adapted for consumer use including the tires and fabricated deck.



### LESS TIME MOWING

Quest mowers offer the value you need as a homeowner. Primarily used for your own property, you need the power, performance, comfort and fuel efficiency of a commercial mower.

## TOP ACCESSORIES

- 2-Bag Collection System
- Assist Bar
- Engine Maintenance Kit
- Equipment Cover
- LED Light Kit
- Micro-Mulch System
- ROPS Kit
- Turf Striping Kit

Accessories may not fit each mower model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

[exmark.com](http://exmark.com)

# QUEST E-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
QZE725GKC42200	Kohler 7000 Series KT725	42"	Series 2 Fabricated	415 lbs.	53.8" x 45.6" x 75.0"
QZE725GKC50200	Kohler 7000 Series KT725	50"	Series 2 Fabricated	576 lbs.	61.7" x 45.6" x 75.0"



## POWER COMPONENTS

**Engine** – Kohler 7000 Series KT725, governed to 3,300 rpm.

**Air Filter** – Standard engine manufacturer's air filter.

**Drive System** – Two Hydro-Gear ZT-2100 hydro static transmissions with no hoses and integrated cooling fans and integrated reservoir.

**Hydro Fluid** – Exmark Premium Hydro Oil.

**Speed** – Infinitely variable speed selection from 0–7.0 mph (11.3 kmph) forward, 0–5.0 mph (8.0 kmph) reverse.

**PTO Engagement** – 42" unit has electromagnetic 80-ft-lb clutch; 50" unit has electromagnetic 105-ft-lb clutch

**Fuel Capacity** – 3.0-gallon (11.0-L) single fuel tank with single fill location.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock.

**Deck Lift** – Standard; hand lever deck lift on 42" and foot assist deck lift on 50" changes cutting height and lifts the deck to maneuver around obstacles, or place in transport position.

## DECK

**Style** – Series 2 fabricated and welded steel deck. Decks have side-discharge standard with the option to bag or mulch.

**Deck Construction** – Series 2 units have 10-gauge top that is formed and welded, 12-gauge side skirt and 7-gauge welded bumper. 3 point suspension.

**Widths Available** – 42" (107 cm) and 50" (127 cm).

**Cutting Height** – 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments, adjustable from operator seat.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles. 5.50"-diameter cutter housing with 17mm- (.67") diameter spindle shaft.

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Tractor Frame** – Unibody, riveted 10-gauge steel.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjustable both fore and aft. Levers are also adjustable to 2-height positions.

**Casters** – .25" thick caster yoke arms.

**Front Caster Tires** – 11 x 4.0-5 smooth-tread, pneumatic on 42" unit; 11 x 6.0-5 smooth-tread, pneumatic on 50" unit.

**Drive Tires** – 18 x 7.50-8, 4-ply Turf Tech TL on 42" unit; 18 x 9.5-8 K500 on 50" unit.

**Turning Radius** – True zero-turn.

**Parking Brake** – Automatic-actuated pawl brake.

**Seat Comfort** – Units have 16" high-back Optional armrests. Hinged mounting with spring suspension. Adjustment fore and aft 3" by loosening 2 bolts and sliding seat.

**Electrical** – 12-volt battery with 15-amp alternator.

**Standard Features** – Cup holder and hitch.

**Optional Features** – Hour meter and seat armrests.

## ACCESSORIES & OPTIONS

2-Bag Collection System, Anti-Blowout Kit, Armrest Kit, Assist Bar Kit, Deck Foot Lift Assist Kit, Equipment Cover, Hour Meter, Jack, Jack Mount Receiver, LED Light Kit, Micro-Mulch System, ROPS Kit, Sunshade, Turf Striping Kit and Weight Kit.

*Accessories may not fit each model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.*

## WARRANTY

Limited Warranty: 30-Day Commercial or 3-Year Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

<sup>1</sup> Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

<sup>2</sup> For complete details, visit [exmark.com](http://exmark.com) or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Quest® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.