



2020 PRODUCTS



Z Turf Equipment™ is part of the Exmark® family of products.



Z TURF EQUIPMENT

PROFITABILITY, PERFORMANCE AND VERSATILITY.

From aeration to spreading and spraying, the Z Turf Equipment encompasses an innovative line of turf management products that provides the versatility and profitability that your business needs. Built with the durability and reliability you've come to expect, it's time to see how the Z Turf Equipment line-up can be the perfect addition to your business.

TAKE ADVANTAGE OF THESE OFFERINGS.

FLEET

Loyalty does have its rewards as you'll receive discounts and extra benefits for purchasing multiple units.

FINANCING

Purchasing ZTurf Equipment products is easy and affordable with special Z Turf Equipment finance promotions available through your participating independent ZTurf Equipment dealer. Apply online or visit your participating ZTurf Equipment dealer today.

PARTS AND SERVICE

Whether you perform your own maintenance or rely on our network of servicing dealers, we have you covered with OEM parts from ZTurf Equipment.



**LEAN-TO-STEER.
EASY TO MANEUVER.
IMPROVED PROFITABILITY.**



The Z-Spray LTS spreader-sprayer is one of the most advanced machines in its category. Extremely easy to operate and maneuver, it features our most advanced lean-to-steer technology, outstanding versatility and amazing stability—even on hillsides. Couple that with outstanding durability and you have a spreader-sprayer that is built to last.



LEAN-TO-STEER TECHNOLOGY

Enables the operator to control speed and direction with one hand, which frees the other hand to adjust spread or spray controls, or perform spot treatments with the easy access spray wand. The intuitive control layout makes the machine easy to operate and make adjustments on the fly.



PROFITABILITY

The 2-in-1 capabilities of the LTS gives operators the choice to spread granular or spray liquid fertilizer with each pass of the machine. With the ability to cover more properties in less time, operators can be more profitable.



VERSATILITY

This machine gives operators the choice to spread or spray efficiently, allowing them to provide the services their customers need, when they need it.

FEATURES



LARGE HOPPER CAPACITY

The large hopper can hold 175 pounds and is equipped with a soft, easy-to-remove cover. The carrier on top of the tank can also hold an extra 50-pound bag of dry material for the spread system.



AGITATION SYSTEM

The in-tank agitation system keeps materials in suspension for even more, consistent coverage. This allows operators to use a wider range of materials, from flowable solids to wettable powders.



STABILITY

Designed for performance, the 53-inch turning radius of this machine also provides operators outstanding stability—even on uneven terrain.



SPRAY TANK

For greater efficiency, a single 20-gallon tank, with one fill location, keeps you spraying longer with fewer fill-ups.

PRODUCTIVITY



DIGITAL CONTROLS

The Z-Spray LTS spreader sprayer offers digital spread and spray controls for easier, more precise application settings. These controls increase application precision, for optimal results and reduced material waste. Constant agitation in the tank ensures materials are kept in suspension for consistent spray performance, even when using wettable powders and other dry-flowable materials.

ACCESSORIES



ANTI-SIPHON ASSEMBLY



HOPPER SCREENS



HOSE TRAY — 15 FT.



MULTIPURPOSE BAG



30-FT. EXTENDED HOSE LENGTH WITH HOSE TRAY



SPRAY WANDS

Also Available:
Additional Spray
Nozzles

Accessories may not fit each model. Please visit zturfequipment.com or check with your dealer on accessory fit-up for each model.



**ZERO-TURN MANEUVERABILITY.
VERSATILE AND PROFITABLE.
FEATURES ADD PRODUCTIVITY.**



One size doesn't fit all when it comes to commercial sprayers and spreaders; that's why Z Turf Equipment offers a complete line of Z-Spray® units to meet your specific needs. With the ability to apply granular and liquid materials simultaneously or separately, these versatile machines are the ultimate resource for your business during your busiest time of the year.



LOCKING CASTERS
The patented locking front caster system helps to protect lawns and provides stability on uneven surfaces, resulting in more consistency.



STAINLESS STEEL CHASSIS
All Z-Sprays feature high-grade corrosive-resistant stainless steel, ensuring your equipment will endure many seasons to come.



NOZZLES
The durable ceramic air induction tips provide low drift application even in windy conditions and can be shut off immediately, giving you the control you need to consistently apply the correct chemicals to the turf.

FEATURES



CALIBRATION
Calibration is made easy, thanks to the conveniently located digital speedometer, liquid filled pressure gauge and helpful calibration chart.



75-FT HOSE REEL
When you need to spot treat or have a hard to reach area, the 75-foot hose reel will give you even more flexibility in the properties you can treat.
(Not available on Jr. 36 or LTS)



FOOT OPERATED SWITCH
Conveniently located to help reduce operator fatigue, the foot operated switch is ideal for situations that require spot spraying.



LIQUID PUMP
Pumping at a rate of 5 gallons per minute, units are capable of spraying up to 1 gallon per 1,000 square feet, dependent on tip size. A 7 gallon-per-minute XL pump is an available accessory.

PRODUCTIVITY



FEATURES THAT ADD UP
The Z-Spray spreader-sprayers were designed to deliver the productivity and ROI that your business needs. With zero-turn maneuverability, they enable operators to quickly and accurately apply the necessary products, in less time, every time. The large capacity hydraulic hoppers range from 120- to 220-pounds of granular capacity and allow operators to vary the spread pattern from 3 to 25-feet. Then add in the additional 100-pound granular capacity with the rear fertilizer boxes on all models, and operators get the job done in less time with fewer trips to the truck. With dual tanks on each unit, the liquid capacity ranges from 24- up to 60-gallons. All zero-turn Z-Spray units feature a three section break-away spray boom that is controlled by DirectoValve® Control Valves. Operators can turn on and off the sections of the boom at any given time to adjust the spray width needed for the job.

AVAILABLE OPTIONS





MAKE IT VERSATILE
To keep the Z-Spray spreader-sprayers working for you all season long, these versatile units can be outfitted with a number of optional attachments. The Z-Spray Max is featuring the following optional accessories:

- 1 7 Gallon Isolated Tank
- 2 7 Gallon Auxiliary Tank
- 3 Foam Marker
- 4 30 Gallon Auxiliary Tank
- 5 7 Gallon-per-minute (gpm) XL Pump and Alternator *(can't be seen)*

Note:
20 Gallon Auxiliary Tank available for Junior 36

COMPARISON CHART

| | |
|--|---|
| |  |
| |  |
| MODEL NO. | ZSL3620 |
| ENGINES | 9.5 HP ¹ Kohler® CH395 Command PRO® |
| FUEL CAPACITY | 1.59 Gallons |
| TRANSMISSION | Hydrostatic |
| SPEED | Up to 5.5 mph |
| REAR TIRES | 18 x 7.5-8 |
| FRAME | Stainless Steel |
| HOPPER CAPACITY | 175 lbs. + 50 lbs. on Spray Tank; 12 VDC, 2 HP Motor |
| SPREAD WIDTH | Adjustable from 4 ft. up to 22 ft. |
| TANK CAPACITY | 20 Gallons |
| PUMP | Remco 3.8 gpm |
| SPRAY RATE | Wide - 0.69 gpm at 30 psi, 0.80 gpm at 40 psi; Narrow - 0.35 gpm at 30 psi, 0.40 gpm at 40 psi |
| SPRAY WIDTH | Wide Spray up to 11 ft. wide; Narrow Spray up to 5 ft. wide |
| GATE WIDTH | 36" |
| ONBOARD INTELLIGENCE | Digital Spreader Speed & Spray Pressure Control |
| WARRANTY <small>For complete details, visit zturfequipment.com or your local dealer</small> | 1-Year Limited |

| | |
|--|--|
| |  |
| |  |
| | ZS3624ZS4230 |
| | 16 HP ¹ Vanguard® |
| | 5 Gallons |
| | Hydrostatic |
| | Up to 7.0 mphUp to 8.0 mph |
| | 18 x 7.5-820 x 8.0-8 |
| | Stainless Steel |
| | 120 lbs. + Two 50 lbs. Fertilizer Trays; Hydraulic Motor150 lbs. + Two 50 lbs. Fertilizer Trays; Hydraulic Motor |
| | Adjustable from 3 ft. up to 25 ft. |
| | 24 Gallons (Two 12-Gallon Tanks)30 Gallons (Two 15-Gallon Tanks) |
| | Remco 5.0 gpm |
| | Capacity per Nozzle 0.22 gpm at 30 psi, 0.25 gpm at 40 psi |
| | 2 ft., 4 ft., 6 ft., or 8 ft |
| | 36"42" |
| | Digital Speedometer |
| | 1-Year Limited |

| | |
|--|---|
| |  |
| |  |
| | ZS4630 |
| | 16 HP ¹ Vanguard |
| | 5 Gallons |
| | Hydrostatic |
| | Up to 8.0 mph |
| | 20 x 10.5-8 |
| | Stainless Steel |
| | 220 lbs. + Two 50 lbs. Fertilizer Trays; Hydraulic Motor |
| | Adjustable from 3 ft. up to 25 ft. |
| | 30 Gallons (Two 15-Gallon Tanks) |
| | Remco 5.0 gpm |
| | Capacity per Nozzle 0.22 gpm at 30 psi, 0.25 gpm at 40 psi |
| | 2 ft., 4 ft., 6 ft., or 8 ft. |
| | 46" |
| | Digital Speedometer |
| | 1-Year Limited |

| | |
|--|---|
| |  |
| |  |
| | ZS5260ZS5260XL |
| | 16 HP ¹ Vanguard |
| | 5 Gallons |
| | Hydrostatic |
| | Up to 8.0 mph |
| | 20 x 10.5-8 |
| | Stainless Steel |
| | 220 lbs. + Two 50 lbs. Fertilizer Trays; Hydraulic Motor |
| | Adjustable from 3 ft. up to 25 ft. |
| | 60 Gallons (Two 30-Gallon Tanks) |
| | Remco 5.0 gpmRemco 7.0 gpm |
| | Capacity per Nozzle 0.22 gpm at 30 psi, 0.25 gpm at 40 psi |
| | 2 ft., 6 ft., 8ft., or 10 ft. |
| | 52" |
| | Digital Speedometer |
| | 1-Year Limited |

¹The gross horsepower of these gasoline engines was laboratory rated at 3600 or 4,000 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower.



**SIMPLE OPERATION.
ZERO-TURN MANEUVERABILITY.
VERSATILE ACCESSORIES.**



Redefining the industry, the Z-Aerate brings new life to the demanding job of aeration. With its innovative design, zero-turn maneuverability, a standard hydraulic drive hopper, and a host of available attachments, the Z-Aerate adds up to a highly profitable machine for your business.



HYDRAULIC DRIVE HOPPER
With 120 pounds of granular capacity, the standard hydraulic drive hopper enables operators to offer over-seeding in conjunction with their aeration process—maximizing the revenue opportunities for their business.



MANEUVERABILITY RESULTS IN PRODUCTIVITY
With zero-turn maneuverability, the Z-Aerate features a full-floating 40 inch split-reel aeration head enabling you to aerate around curvy beds and sidewalks without lifting the head out of the ground. The removable weights also allow you to easily adjust for wet or dry soil conditions.



COMMERCIAL DURABILITY
Powered by a commercial-grade Vanguard engine, and a proven Hydro-Gear pump and Parker wheel motor combination, you can be confident this durable machine will endure many seasons to come.

FEATURES



SIMPLE OPERATION
The up-down aeration head lift controls are ergonomically located in the ends of the joysticks—resulting in easy operation and a decrease in operator fatigue.



LOCKING CASTERS
The patented locking front caster system helps to protect lawns and provides stability on uneven surfaces, resulting in more consistency.



FUEL CAPACITY
The large capacity, 5-gallon fuel tank results in fewer trips back to the truck so you can aerate longer with fewer fill-ups.



CORE QUALITY
Featuring thirty, 3/4-inch hardened tines per side, the Z-Aerate utilizes a powerful hydraulic down force system in addition to the weight of the machine to pull up to 3 1/2-inch plugs.



MODEL NO.

ZA4640

ENGINE

18 HP¹ Vanguard

WORKING WIDTH

40"

FUEL CAPACITY

5 Gallons

TRANSMISSION

Pump and Wheel Motor

TIRES

**Front Tires: 13 x 6.5-6 Ribbed Pneumatic
Rear Tires: 20 x 10.5-8**

SPEED

Up to 8.0 mph

NUMBER OF TINES

60 Coring Tines

CORE DEPTH

.5" to 3.5"

WARRANTY

For complete details, visit zturfequipment.com or your local dealer

1-Year Limited

AVAILABLE ACCESSORIES



30 GALLON SPRAY SYSTEM



36-INCH SLICE SEEDER



46-INCH DETHATCH RAKE

Also Available:
40-inch Spike Style Aeration Head

Accessories may not fit each model. Please visit zturfequipment.com or check with your dealer on accessory fit-up for each model.

¹The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers may be significantly lower.

THE PERFECT FIT EVERY TIME.

Z TURF EQUIPMENT OEM PARTS.

You can rest assured knowing your machine is built with the parts engineered specifically for it. As products evolve, you can be confident OEM parts will fit like a glove and keep you up and running for a long time to come. From specially-formulated performance products like engine oil, to sprayer pumps and nozzles, we have you covered. Contact your local dealer to find the perfect fit for your machine.



Z Turf Equipment

415 Industrial Row | Beatrice, NE 68310 | 402.223.6300 | www.zturfequipment.com [f](#) [t](#) [in](#) [@](#)

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. For additional product information including operation manuals, safety materials and warranty details, please visit www.zturfequipment.com or see your dealer for complete details.

¹The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J2723. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these units may be significantly lower.

Many manufacturers use 100% efficiency ratings for sale purposes. Z Turf Equipment believes an 80% efficiency rating is more representative of actual conditions, as it allows for turns and overlapping. Formulas for calculating 1,000 Square Feet Per Hour Productivity: **100% efficiency:** MPH x Aerating width x 0.44 | **80% efficiency:** MPH x Aerating width x 0.352

Z-Spray® is a registered trademark, Z-Aerate™ and Z Turf Equipment™ are trademarks of Exmark Mfg. Co., Inc. Kohler® is a registered trademark and Kohler® Command PRO® is a trademark of Kohler Co. Vanguard® is a registered trademark of Briggs and Stratton. Hydro-Gear® is a registered trademark of Hydro-Gear. DirectoValve® is a registered trademark of TeeJet® Technologies.

© 2020 Exmark Manufacturing Company, Inc. All rights reserved. Printed in the U.S.A. 2020. Form No. 142-3332